

Super Wash[™] Electronics Cleaner 406B Technical Data Sheet

Description

The 406B Super Wash[™] Electronics Cleaner is a very fast drying and zero residue cleaner degreaser for PC boards. This hydrocarbon-based cleaner is perfect for quick PC boards cleaning. When used as a secondary rinse, it accelerates the drying time of boards treated with slower drying cleaners. Great for dissolving many types of flux. Cleans and degreases printed circuit boards, machinery, electrical and electronic devices.

Features and Benefits

- Suitable for Use in Food Facilities as a Non-Food Chemical—Canadian and NFS recognition letters available on request
- Safe on many plastics
- Zero residue
- Fast evaporation rate
- Dissolves oils and residues
- A variable valve on the aerosol lets you adjust the flow rate as needed
- RoHS compliant

ATTENTION!

Do NOT use on live circuits. For use on equipment that will not tolerate aqueous cleaning solutions. Not for use in direct contact with food.

Usage Parameters

Properties	Value
Shelf Life	5 y

Temperature Ranges

Properties	Value
Storage Temperature	-20 to 40 °C
Limits ^{a)}	[-4 to 104 °F]

a) Storage below zero is not necessary. Cool, dry, and well ventilated area recommended.

Properties

Physical Properties	Method	Value
High Purity		No residue
Color		Clear
Odor	—	Mild hydrocarbon
Density @25°C [77 °F]		0.66 g/mL
Viscosity @25°C [77 °F]	Brookfield SP1	0.3 cP [0.0003 Pa·s]
Flash Point	Closed Cup	-29 °C [-20 °F]
Boiling Point		52 °C [126 °F]
Vapor Pressure @25°C [77 °F]		33 kPa [250 mmHg]
Relative Evaporation Rate		0.8 (Ether = 1); 9.4 (ButAc=1)
Volatile Organic Content (VOC)		100%



Solvation Parameters	Value	
Solubility in Water	Insoluble	
KB (Kauri Butanol) Value	30	
Hansen Solubility Parameters ^{a)}	(MPa) ^{1/2}	[cal/cm ³] ^{1/2}
Total	14.9	7.28
Non-Polar	14.9	7.28
Polar	0.0	0.0
Hydrogen Bonding	0.0	0.0

a) Hansen parameters calculate using component literature values and volume fraction composition.

Compatibility

Substrate Compatibility: Consult 406B partial compatibility chart table for substrate compatibility. It is always recommended to perform a compatibility test on a non-critical test area prior to large scale applications. Perform this test even if the chart predicts high compatibility since modern plastic parts may incorporated hidden incompatible materials in the form of plastic blends or as protective and decorative coatings.

Compatibility Chart

Plastic type	Resistance
Ероху	Very Good
ABS (acrylonitrile butadiene styrene	Poor
PMMA (Acrylic)	Good
PVC (Polyvinyl chloride)	Good
HD-PE (high density polyethylene)	Good
LD-PE (low density polyethylene)	Partial
PP (polypropylene)	Good
PS (polystyrene)	Partial
PC (Polycarbonate)	Poor

ATTENTION!

Use with care on thin plastics or near parts that are chemically sensitive.

Solvent Miscibility: The 406B is generally miscible organic solvent, but it is immiscible with water.



Health, Safety, and Environmental Awareness

Please see the 406B **Safety Data Sheet** (SDS) for more details on transportation, storage, handling and other security guidelines.

Health and Safety: This liquid is highly flammable and should be kept away from flames and other ignition sources. Avoid breathing in fumes or direct contact with the material.

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend: 0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Environmental Impact: It is RoHS compliant.

Application Instructions

To clean residues in aerosol format

- 1. Spray dirty area.
- 2. Ensure that wash runs off the circuit board along the shortest unencumbered path to prevent redeposit of solvated residues

Packaging and Supporting Products

406B-425G Aerosol 590 mL 20.0 fl oz	495 449	
	425 g 14.9 oz	5.72 kg ^{a)} 12.6 lb ^{a)}

a) Case pack of ten

Supporting Products

- *Hog Hair Cleaning Brush*: Cat. No. 852
- Large Hog Hair Cleaning Brush: Cat. No. 853



Technical Support

Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at <u>www.mgchemicals.com</u>.

Email: support@mgchemicals.com

Phone: +(1) 800-340-0772 (Canada, Mexico & USA) +(1) 905-331-1396 (International) Fax: +(1) 905-331-2862 or +(1) 800-340-0773

Mailing address: Manufacturing & Support 1210 Corporate Drive Burlington, Ontario, Canada L7L 5R6 Head Office 9347–193rd Street Surrey, British Columbia, Canada V4N 4E7

Warranty

M.G. Chemicals Ltd. warranties this product for 12 months from the date of purchase by the end user. *M.G. Chemicals Ltd.* makes no claims as to shelf life of this product for the warranty. The liability of *M.G. Chemicals Ltd.* whether based on its warranty, contracts, or otherwise shall in no case include incidental or consequential damage.

Disclaimer

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. *M.G. Chemicals Ltd.* does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.